

TEAMTEC INCINERATORS

Market leaders since 1972 - More than 11 000 units sold worldwide



OG400CS with a sluice for continuous feeding of solid waste. Capacity: 596 kW

TEAMTEC Incinerator model OG400C

With its sturdy and compact design and high performance the **OG400C** is one of our most popular models and an *obvious first choice* for solving the waste treatment on-board medium-sized vessels.

COMPACT DESIGN

The TEAMTEC high capacity incinerator models have one of the world's **smallest footprints and overall size**. The incinerators can easily be installed in a corner.

Our incinerators are made from high quality marine components only.

AUTOMATIC CONTROL

TEAMTEC incinerators are all controlled by a state-of-the-art PLC ensuring a **simple and reliable operation, maximum capacity utilisation and minimum fuel consumption**.

Minimum attendance is needed during operation and remote supervision is possible.

LOW OPERATION COSTS


Our unique high temperature cyclone burning principle ensures that all the incinerators in TEAMTEC product range can incinerate sludge oil (waste oil) with water content up to 50% without using support fuel, leaving our incinerators as one of the most **economical** incinerators on the market.

TEAMTEC incinerators have **no strainers or filters** in the sludge oil system and this in addition to several other advantages keeps the maintenance costs to an absolute minimum.

MODULAR CONSTRUCTION

All our incinerators are of a **modular construction** and can, if required, be delivered as a flat-packed unit for assembling onboard the vessel/installation – no parts are bigger than a normal ship door. No welding is needed.

This construction also benefits the life-time maintenance works.



MED APPROVED


TECHNICAL DATA – OG400C model:

version :	C	CS	CW	CSW	CI*	CIS*
Calorific capacity:	512 000 kcal/h 596 kW	512 000 kcal/h 596 kW	512 000 kcal/h 596 kW	512 000 kcal/h 596 kW	625 300 kcal/h 727 kW	625 300 kcal/h 727 kW
Sludge oil capacity **:	74 l/h	74 l/h	N/A	N/A	81 l/h	81 l/h
Bilge water capacity:	N/A	N/A	N/A	N/A	140 l/h	140 l/h
Solid waste capacity:	400 l/load (52 kg IMO***)	20-50 kg/h	400 l/load (52 kg IMO***)	20-50 kg/h	400 l/load (52 kg IMO***)	20-50 kg/h
Feeding sluice:	-	Yes	-	Yes	-	Yes

* With TEAMTEC water injection system. ** IMO-defined sludge oil, 20% water content.

All versions (except CW and CSW) burn simultaneously sludge oil and solid waste.

TEAMTEC incinerators are designed and certified in compliance with the IMO resolution MEPC 76 (40) and IMO MARPOL ANNEX VI.



PLC colour touch screen panel as standard

OPTIONS:

- Skid/base mounted units
- Containerized units
- Remote control panel / slave panel
- Sludge oil and diesel oil tanks
- Diesel oil transfer and booster pumps
- Sludge tank level indicator in operator display
- Heat tracing control for the sludge circulation line
- Frequency controlled flue gas fan
- Flue gas stack components
- Solutions for ambient temp. above 55°C
- Project versions

BILGE WATER INJECTION:

As an option the incinerator can be equipped with TEAMTEC bilge water injection system to reduce the load on the Oily Water Separator by utilizing the heat from the sludge oil combustion. No additional diesel oil consumption.

With PLC controlled injection of the water while burning sludge oil, you achieve:

- Safe disposal of contaminated water
- Increased sludge capacity (ref. table)
- Reduced NOx emission - verified by DNV

Bilge water injection is approved by major classification societies.

Quick and simple upgrading of existing TEAMTEC incinerators is available.

TG5.2 – Aug, 2017